

Syntilor **Nature Protect® Worktop Oil** is a genuine conditioning balm, specially designed for your wooden worktops. It nourishes and protects the wood from the repeated damage of everyday use. A green formulation with no compromise on quality.

- All types of wood
- Worktops
  - For indoor use



### **PREPARATION**

- Old woodwork should be stripped using Syntilor Décapant stripper Or Syntilor Décireur wax remover, to
  ensure the wood is clean and free of stains (oil, polish and wax, old varnish, woodstain,
  paint, etc.), then sanded (sandpaper grade 40, 60 then 100).
- If necessary, use a suitable wood treatment product.
- New or bare wood should be finely sanded using sandpaper (120 grade).
   Dust thoroughly.
- For exotic or oily wood, degrease with acetone.

## 2

### **APPLICATION**

- Shake the container well before use.
- Apply with a brush in thin coats.
- Wipe off the excess with a cotton rag (work in the direction of the wood grain) used only for this purpose.
- Leave to dry for 2 hours then sand lightly (120 grade) before applying the next coat.
- Repeat the application, 3 coats are needed to protect the wood properly.

# 3

### **MAINTENANCE**

- For wood that has already been oiled with Syntilor **Nature Protect® Worktop Oil,** sand lightly with 120 grade sandpaper then apply a new, very thin coat.
- Do not apply to wood that has already been treated with traditional oil.





# TECHNICAL SPECIFICATIONS

RESIN TYPE	High-performance emulsified oil
DENSITY	1.02
CONSISTENCY	Fluid liquid
DRYING TIME (at 20° C)	Touch dry: 1 hr Between coats: 2 hrs Fully dry: 12 hrs
COVERAGE	20 m² per litre per coat
FINISH	Matt

The environmental product declaration for Nature Protect® worktop oil has been filed on the site www.declarationenvironnementale.gouv.fr and can be consulted on our site www.syntilor.com

- Apply to sound, clean and dry surfaces.
- Use outdoors or in a well-ventilated area only.
- Do not apply at a temperature below 12° C or above 25° C.
- Keep out of reach of children.
- Store in the original packaging, carefully closed after use.
- Store away from frost, heat and humidity.
- The Safety Data Sheet for this product is available at www.syntilor.com

### **TOOLS**

### **TOOL CLEANING**





