



WAXED-EFFECT, MATT AND GLOSSY WOOD VARNISHES

Syntilor Waxed-Effect, Matt and Glossy Wood Varnishes are made of very high-quality polyurethane resins that give them exceptional resistance to stains, knocks and scratches. Meticulously formulated, they protect all interior furniture and woodwork (utilitarian and decorative furniture, door frames, beams, etc.). They provide remarkable resistance and a warm, high-quality and velvety appearance.

- Long-lasting protection: very nourishing
- Perfect rendering
- Specially formulated for indoor use

1

STEP

PREPARATION

- **Old wood:** apply Syntilor Stripper to strip the wood so it is clean, with no trace of old finishes. Sand with 80–120-grit sandpaper, then dust thoroughly.
- **New or bare wood:** sand using fine sandpaper (120 grit). Dust thoroughly.
- If necessary, treat with a suitable wood-treatment product.

2

STEP

APPLICATION

- Ready to use, do not dilute.
- Stir well before use.
- Using a paint brush, apply 3 thick coats, following the direction of the wood grain.
- Between each coat: leave to dry for 2 hours, sand lightly (120–180-grit sandpaper) then dust thoroughly.
- For the first 10 days after treatment, avoid cleaning and take particular care to avoid knocks.

3



STEP

MAINTENANCE

- Clean with a damp (non-abrasive) sponge and mild detergent.



TECHNICAL CHARACTERISTICS


TYPE OF RESIN	Water-based polyurethane resin
DENSITY	1.02 (± 0.05 depending on the colour)
CONSISTENCY	Smooth
DRYING TIME (at 20°C)	Touch dry: 30 minutes Between coats: 2 hours Fully dry: 24 hours
YIELS	12m ² per litre per coat
ASPECT	Waxed-effect, Matt and Glossy
HEALTH & SAFETY LABELLING	 <p>* Information on the emission level of volatile substances in indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).</p>
ECOLABEL	 <p>EU Ecolabel: FR/044/011</p>

PRECAUTIONS & STORAGE

- Application on sound, clean and dry surfaces.
- Use only outdoors or in a well-ventilated area.
- Do not apply at temperatures below 12°C or above 25°C.
- Keep out of the reach of children.
- Store in the original packaging, carefully closed after use.
- Store away from frost, heat and humidity.
- The Safety Data Sheet for this product is available at www.syntilor.com

TOOLS & CLEANING

TOOLS



CLEANING TOOLS

